


CONNECTING
VISIONS



www.ftg-germany.de



Auxiclic

Flexible system for 250A busbars

Product information

Auxiclic

Auxiclic is a 250A busbar intended to supply a row of modular devices, max. current rating for every output is 63 A. Each connector locks automatically, this guarantees high security, no risk of direct contact, according to IP20.

Ratings:

■ Busbar: 250A / 690v
■ Short-circuit values: I _{pk} : 61 kA / I _{cw} : 10 kA / 1 s
■ Connector 6mm ² : 40 A
■ Connector 10 mm ² : 63 A

Modularity

■ Supply with wires and ring terminals, flexible bars or directly on the flat copper bars of the main busbar
■ Due to its high strength, Auxiclic can be used as a busbar support
■ Length: 12, 24, 36 Modules
■ Fixing on the sides of the cabinet or on double-DIN rail

Live maintenance

■ Each connection to the device is simply achieved with a connector, no screw to tighten.
■ Phase balancing, addition, live modification.

Security

■ Each connector locks automatically.
■ The locking is guaranteed by a CLIC.
■ No risk of direct contact. IP20

Auxiclic can easily be adapted to your requirements:

■ Fixings specific to your cabinet
■ Possible length up to 36 Modules
■ Color of the connector wires: brown, red, white
■ Length of the wires
■ Termination of the wires: pre stripped, with ferrule or ultrasonic welded


Connectors



With flexible wires 6 mm² type H07VK

Packing unit 10 pieces

■ black, with ferrule 120 mm	# 96505
■ blue, with ferrule 120 mm	# 96506
■ black, 320 mm	# 96509
■ blue, 320 mm	# 96510
■ black, 500 mm	# 96519
■ blue, 500 mm	# 96520
■ black, 1000 mm	# 96527
■ blue, 1000 mm	# 96528



With flexible wires 10 mm² type H07VK

Packing unit 10 pieces

■ black, with ferrule 120 mm	# 96507
■ blue, with ferrule 120 mm	# 96508
■ black, 320 mm	# 96511
■ blue, 320 mm	# 96512
■ black, 500 mm	# 96521
■ blue, 500 mm	# 96522
■ black, 1000 mm	# 96523
■ blue, 1000 mm	# 96524



Connector with crimp terminal

Packing unit 20 pieces

For wire 1.5 to 2.5 mm ²	# 96530
For wire 4 to 6 mm ²	# 96529

Auxiclic

Part #	Dimensions	Description	Packing unit
AUXCL12	233 x 40 x 45 mm	6 connections per phase / 12 for Neutral 12 Modules (18 mm)	1 pcs.
AUXCL24	422 x 40 x 45 mm	12 connections per phase / 24 for Neutral 24 Modules (18 mm)	1 pcs.
AUXCL36	616 x 40 x 45 mm	18 connections per phase / 36 for Neutral 36 Modules (18 mm)	1 pcs.

